



GONGDA GROUP LIMITED

TEL: 0086-22-24312818 EMAIL: INFO@GDG-PLYWOOD.COM WEB: WWW.GDG-PLYWOOD.COM

PINE PLYWOOD

Brief Instruction:

Pine Plywood is made with 100% Pine or Pine Face/Back and Poplar Core. Pine wood is a kind of soft wood which grows in worldwide, so the Pine Plywood was used most in worldwide. Such as CDX or Lower Grade Plywood can be used as shuttering formwork. Also High grade Pine Veneeres has beautiful Grains, it is also very good materials for Cabinet or Furniture Making.

Specification:

Face/Back&Grade	Core Materials	Glue	Size	Thickness	Grade
1) Chinese Pine 2) Radiated Pine 3) UV Prefinished Pine	1) 100% Pine 2) 100% Poplar 3) Combi of Pine&Poplar	1) WBP 2) MR&E0 3) MR&E1 4) MR&E2	1200*1800MM	3-50MM	1) BB/CC 2) C/D 3) D/E 4) UT Y
			1200*2400MM		
			1220*2440MM		
			1250*2500MM		
			1525*1525MM		
			1525X3050MM		
1500*3000MM					

FLORRING BASE PLYWOOD

Brief Instruction:

Flooring Base Panel is only for Flooring Making. Depended on the different request on density and hardness, many wood species are applicable such as white birch, poplar, hardwood. Due to high quality requirement, On Flooring Panel, each layer is average thickness, no core void and overlaps allowed to prevent water of moisture entering into. Normally, the Glue request excellent bonding and also low emission of formaldehyde.

Specification:

Face/Back&Grade	Core Materials	Glue	Size	Thickness	Grade
None	1) 100% Poplar Core 2) 100% Birch Core	WBP&E1	915*1830MM	6-30MM	None
			915*1220MM		
			1220*1830MM		
			1220*2440MM		

Contact Infomation

Contact: Export Department
 Contact Email: info@gdg-plywood.com
 Webpage: www.gdg-plywood.com
 Office Tel: 86-22-24312818